

Discounted UCB

Levente Kocsis and Csaba Szepesvári

MTA SZTAKI, Hungary

UCB1-tuned

Discounted UCB1-tuned

Experiments

Other algorithms

Conclusions

UCB1-tuned+

$$s_{it} = \sum_{\tau=0}^t \mathbb{I}(l_\tau = i) x_\tau$$

$$n_{it} = \sum_{\tau=0}^t \mathbb{I}(l_\tau = i)$$

$$\mu_{it} = s_{it}/n_{it} \quad n_t = \sum_i n_{it}$$

$$l_{t+1} = \operatorname{argmax}_i \left(\mu_{it} + \sqrt{\frac{\max(\mu_{it}(1 - \mu_{it}), 0.002) \ln n_t}{n_{it}}} \right)$$

Discounted UCB1-tuned+


$$s_{it} = \sum_{\tau=0}^t \mathbb{I}(l_\tau = i) \gamma^{t-\tau} x_\tau$$

$$n_{it} = \sum_{\tau=0}^t \mathbb{I}(l_\tau = i) \gamma^{t-\tau}$$


$$\mu_{it} = s_{it}/n_{it} \quad n_t = \sum_i n_{it}$$

$$l_{t+1} = \operatorname{argmax}_i \left(\mu_{it} + \sqrt{\frac{\max(\mu_{it}(1 - \mu_{it}), 0.002) \ln n_t}{n_{it}}} \right)$$


Experiments: Task 1 (averaged over 1000 seeds)




Experiments: Task 1 (averaged over test seeds)




Experiments: Task 2 (averaged over 1000 seeds)




Experiments: Task 2 (averaged over test seeds)



Experiments: Task 3 (averaged over 1000 seeds)



Experiments: Task 3 (averaged over test seeds)



Other algorithms

- ▶ line fitting
- ▶ discounted UCB + exploiting periodicity
- ▶ adaptive discounted UCB

Conclusions

- ▶ Challenging challenge
- ▶ Task 4(?): mixing task 1 and 2
- ▶ Regret bounds depending on how fast the response rate vary?
- ▶ Universal algorithms (algorithms adapting to response rate)