Subclasses

Subclass = special case = fewer entities/objects = more properties.

- Example: Ales are a kind of beer. In addition to the properties (= attributes, relationships, methods) of beers, there is a "color" attribute for ales.

ODL Subclasses

Follow name of subclass by colon and its superclass.

```
interface Ales:Beers {
    attribute String color;
}
```

- Objects of the `Ales` class acquire all the attributes and relationships of the `Beers` class.

E/R Subclasses

- *isa* triangles indicate the subclass relation.



Difference in Subclass Viewpoints

- In ODL, an object is in exactly one class.
  - ❖ It inherits properties of its superclass(es).
- In E/R, an entity has "representation" in all the subclasses to which it logically belongs.
  - ❖ Its properties are the union of the properties of these classes.
- The distinction matters later, when we convert ODL and E/R to relations.



Multiple Inheritance

Theoretically, a class/E.S. could be a subclass of several classes.



Problems

How should conflicts be resolved?

- Example: `manf` means grower for wines, bottler for beers. What does `manf` mean for "grape beers"?
- E/R mute on multiple inheritance; ODL leaves it to implementer.

Keys

= set of attributes whose values can belong to at most one entity or object.

- In E/R: underline all key attributes.
- In E/R, each E.S. must have a key.
- Example: Suppose `name` is key for *Beers*.



- Beer name is also key for ales.
  - ❖ In general, key at root is key for all.

Keys in ODL

Indicate with `key(s)` following the class name, and a list of attributes forming the key.

- ❖ Several lists may be used to indicate several alternative keys.
- ❖ Parentheses group members of a key, and also group `key` to the declared keys.
- ❖ Thus, `(key(`$a_1, a_2, \ldots, a_n$`))` = "one key consisting of all n attributes." `(key` $a_1, a_2, \ldots, a_n$`)` = "each a_i is a key by itself.

- Example:

```
interface Beers
    (key name)
{
    attribute string name ...
```

A Multiattribute Key




```
interface Courses
    (key (dept, number), (room, hours))
{
    ...
```

- E/R requires exactly one key, but ODL allows zero or more keys.
- **Very Important**: In ODL, "object identity" serves to distinguish objects, so *no key at all is necessary.*

Weak Entity Sets

Sometimes an E.S.'s key comes not (completely) from its own attributes, but from the keys of one or more E.S's to which the first is linked by a many-one relationship.

- Called a *weak* E.S.
- Represented by putting double rectangle around the weak E.S. and a double diamond around each relationship to which the weak E.S. is linked to an E.S. that provides part of its key.
- Use of many-one relationship (includes 1-1) essential.
  - ❖ With a many-many, we wouldn't know which entity provided the key value.
- **Very Important**: There is no such thing as a "weak class" in ODL.
  - ❖ Because objects have object-identity, classes don't need keys, and therefore they don't need to "borrow" keys from related classes.

Example: Logins (Email Addresses)

Login name = user name + host name, e.g., `ullman@shalmaneser.stanford.edu`.

- A "login" entity corresponds to a user name on a particular host, but the passwd table doesn't record the host, just the user name, e.g. `ullman`.
- Key for a login = the user name at the host (which is unique for that host only) + the IP address of the host (which is unique globally).



Example: Chain of "Weakness"

Consider IP addresses consisting of a primary domain (e.g., `edu`) subdomain (e.g., `stanford`), and host (e.g. `shalmaneser`).



- Key for primary domain = its name.
- Key for secondary domain = its name + name of primary domain.
- Key for host = its name + key of secondary domain = its name + name of secondary domain + name of primary domain.

All "Connecting" Entity Sets Are Weak



- In this special case, where bar and beer determine a price, we can omit `price` from the key, and remove the double diamond from `ThePrice`.
- Better: `price` is attribute of `BBP`.

Design Principles

Setting: client has (possibly vague) idea of what he/she wants. You must design a database that represents these thoughts and only these thoughts.

- Avoid redundancy.
  - ❖ Wastes space and encourages inconsistency.
- KISS = keep it simple, students.
  - ❖ Avoid intermediate concepts.
- Faithfulness to requirements.
  - ❖ Remember the design *schema* should enforce as many constraints as possible. Don't rely on future data to follow assumptions.
  - ❖ Example: If registrar wants to associate only one instructor with a course, don't allow sets of instructors and count on departments to enter only one instructor per course.

Example

Good:



Bad (redundancy): repeats manufacturer address for each beer they manufacture.



Bad (needless intermediate):



- Question: Why is it OK to have *Beers* with just its key as attribute? Why not make set of beers an attribute of manufacturers?
  - ❖ Questionable in E/R, but clearly legal in ODL:

```
interface Manfs (key name) {
    attribute string name;
    attribute string addr;
    attribute Set<string> beersManfed;
}
```