Preparing for the final exam

Exam material

UI Programming: Widgets, Events, Listeners, Model-View-Controller (MVC) architecture

Modeling user interaction, state machines

UI Design principles: C.R.A.P., gestalt laws, perfomance & memory

User-centered design & evaluation: conceptual models, feedback, scenarios, sketches, and storyboards, evaluation & usability criteria

Phrasing and chunking, modes & gestures

Input: Direct, indirect, relative, absolute pointing, CD gains, multitouch

Additional information

Duration: 2 hours

Authorized material: any document in paper form

Language: either English or French

Widgets, event-based programming, and MVC

Exam 2013 – A.

Identify the components (widgets), their events, and their listeners

Save in: 🌙 alertbox	• 😳 🦻 🕑 🕻		
Name	Size		
government-nonprofit-dmv-site.png	22 KB		
government-nonprofit-va.png	37 KB		
sarasota-ballot-superimposed-screen	125 KB		
time_spent_per_site_b2b_example.png	37 KB		
traffic_incoming_queries.png	43 KB		
traffic_incoming_queries_length.png	24 KB		
traffic_page_popularity_zipf.png	55 KB		
traffic_referrals_from_other_sites.png	48 KB		
usability_methods_usage_trend.png	11 KB		
File name: sarasota-ballot-superimposed-screens	png	Save	
Save as type: PNG - Portable Network Graphics	•	Cancel	

You don't necessarily have to follow the naming and precise structure of Swing

Hierarchy of Swing components



Save in: 🎍 alertbox	• 😳 🗭 📂 🛄 •	,
Name	Size	
government-nonprofit-dmv-site.png	22 KB	
government-nonprofit-va.png	37 KB	
sarasota-ballot-superimposed-screen	125 KB	
time_spent_per_site_b2b_example.png	37 KB	
traffic_incoming_queries.png	43 KB	
traffic_incoming_queries_length.png	24 KB	
traffic_page_popularity_zipf.png	55 KB	
traffic_referrals_from_other_sites.png	48 KB	
usability_methods_usage_trend.png	11 KB	
le name: sarasota ballot superimposed screens p	ng Sav	•
ave as type: PNG - Portable Network Graphics	• Cano	:el

Can you create the hierarchy of the containers and components of this UI?



What about the events and their listeners? Example: Think about how to handle selection events within the list (tabular form) of the files

Exam 2013 - B (MVC)



Figure 2— In this example a user is approaching a digital table with their mobile. A halo appears at the edge of the mobile. The user can flick the image towards the halo. When the image slides off the edge of the mobile it is disappears and reappears on the table.

Exam 2013 - B (MVC)



Where is the application? In the mobile device or in the tabletop?

Exam 2013 - B (MVC)



Where is the application? In the mobile device or in the tabletop?

Create a diagram that shows the interaction between the View, the Controller, and the Model for the mobile device and the tabletop application.

remember...



remember...



remember...



But this is not the only possible flow of messages. For example, when the user moves the picture from the mobile phone to the halo, it is the controller of the tabletop application that detects the change. There is no notification from the view.

State machines





Modeling interation: state machines

The touch surface of a smartphone detects the contact point of a single finger.

The surface sends events when the finger touches the surface (FingerDownEvent), slides on the surface (FingerDragEvent) or leaves the surface (FingerUpEvent). Each event contains the coordinates of the contact point and a value that represents the time (in milliseconds) from the beginning of the session.

To facilitate the programming of interaction with graphical objects (widgets) of the UI of the smartphone, we decided to create a layer of events at the level of the widgets. More precisely, events at this level are produced when the finger touches a widget (OnWidgetEvent), taps on a widget (TapWidgetEvent), moves on a widget (DragWidgetEvent), stays on the widget for more than T = 300 ms (PauseWidgetEvent) or is raised from the widget (ReleaseWidgetEvent).



The touch surface of a smartphone detects the contact point of a single finger.

The surface sends events when the finger touches the surface (FingerDownEvent), slides on the surface (FingerDragEvent) or leaves the surface (FingerUpEvent). Each event contains the coordinates of the contact point and a value that represents the time (in milliseconds) from the beginning of the session.

To facilitate the programming of interaction with graphical objects (widgets) of the UI of the smartphone, we decided to create a layer of events at the level of the widgets. More precisely, events at this level are produced when the finger touches a widget (OnWidgetEvent), taps on a widget (TapWidgetEvent), moves on a widget (DragWidgetEvent), stays on the widget for more than T = 300 ms (PauseWidgetEvent) or is raised from the widget (ReleaseWidgetEvent).

Define a state machine that manages the creation of the events OnWidgetEvent, TapWidgetEvent, DragWidgetEvent, PauseWidgetEvent, and ReleaseWidgetEvent.

Assume that a TapWidgetEvent is created when the delay between an event OnWidgetEvent and an event ReleaseWidgetEvent is less than T = 300 ms and there is no significant finger movement (Dmin < 5 mm).

Solution



Solution



Exam 2012-A

Create a state machine for the three techniques:

- Area cursor: area around cursor, can click on targets when inside
- Bubble cursor: closest target always selected on click
- Dynaspot:
 - area cursor of MAXWIDTH active when speed > MAXSPEED
 - when speed drops an animation starts that takes REDUCETIME during which the area of the cursor becomes smaller until 0 and the cursor becomes a regular cursor
 - during REDUCETIME we can accelerate, and go to area cursor

Can use:

- List = IntersectTargets (mousePos, WIDTH)
- Target = ClosestTarget (mousePos, List)
- ResetTimer(), GetTime (): start a timer and see time passed
- TimeOut (programmable) event to start after n sec with Arm(n), a fuction Disarm() cancels the Arm call if TimeOut has not started



Other examples:

You may be asked to create a state machine that desribes a small set of multitouch gestures or a technique for mid-air interaction.

Models of user performance

Menus



Discuss the advantages & disadvantages of different ways of improving a menu design:

- [1] Double the height of the menu items
- [2] Order the menu items in alphabetic order
- [3] Order the menu items by frequency of use
- [4] Group the items based on their semantics

Use criteria from human performance and models or laws to justify your analysis

Fitts' law



Fitts' law



Top better because all buttons are bigger

or

Bottom better because "back" is more frequent

Hick-Hyman's law

Describes the time to take a simple decision as a function of number of choices

 $T = a + b \cdot \log_2(n+1)$



n : number of choices *a*, *b* : constants

We divide the total number of choices and re - search : binary search

Other factors?

memorisation

visual search

...

Enlarging the height of the items



Enlarging the height of the items



Enlarging the height of the items



 $W_2 = \alpha \cdot W_1 \Longrightarrow D_2 = \alpha \cdot D_1$ $\Longrightarrow T_2 = T_1$

Enlarging the height of the items



Other factors that may affect performance ?

Enlarging the height of the items



How do things change if we also consider submenus?

Alphabetical order



Find France !

Allemagne
Bulgarie
Italie
Pologne
Espagne
France
Belarus

Norvège

Irlande

Islande

Lettonie

linear

Alphabetical order



Disadvantages?

Selection frequency

Benefits acording to Fitts' law ?

$$\overline{T} = \sum_{i=1}^{N} (a + b \cdot \log_2(\frac{D_i}{W} + 1)) / N$$

Is the mean movement time different?

Selection frequency

And the time for visual search ?

factors

... before and after the « stabilization » of frequencies ... distribution of selections

and memorization of the item position ?

Semantic grouping

Advantages and disadvantages ?

Affighage	Insertion	Format	Outils	Diaporama
 Normal Trieuse o Page de Outils du 	de diapositiv commentair 1 présentate	ves es ur		3.0
Diaporar	na			
Masque				•
En-tête e Afficher Nuances	et pied de p les commen de gris	age taires		
Boîte à o ✓ 団 Pi ₩0 O	utils alette de mi bject Palette ersonnaliser	se en forn e · l'animati	ne on	
∰ A Ⅲ O ペ R ● P:	lbum utils de réfé apport de ce alette de pro	rence ompatibili ojet	té	∖C≋R
Bibliothè Barres d' Personna	que d'éléme outils aliser les bai	ents rres d'outi	ls et les	► menus
✓ Règle Repère Zoom				Þ

Semantic grouping

Which gestalt principles have been applied to this menu design?

Affichage	Insertion	Format	Outils	Diaporama
✓ Normal				
Trieuse o	de diapositiv	/es		
Page de	commentair	es		
Outils du	i présentate	ur		
Diaporar	na			
Masque				Þ
En-tête e	et pied de p	age		
Afficher	les commen	taires		
Nuances	de gris			
Boîte à o	utils			
√ 🔤 P;	alette de mi	se en forn	ne	
M6 0	biect Palette			
it P	ersonnaliser	l'animati	on	
	lhum			
ibili o	utile do rófé	ronco		7 ⁻ 9₽ D
1000 0	utils de l'ele	inence		CORK
R	apport de co	ompatibili	te	
🗎 Pa	alette de pro	ojet		
Bibliothè	que d'éléme	ents		
Barres d'	outils			•
Personna	aliser les bai	rres d'outi	ls et les	menus
✓ Rèale				
Repère				Þ
Zoom				

Gestalt laws of perception

Continuity Proximity Similarity Symmetry Closure Common Fate

etc...

Gestalt laws of perception

Continuity Proximity Similarity Symmetry Closure Common Fate

etc...



Gestalt laws of perception

Continuity 🖌
Proximity 🖌
Similarity 🖌
Symmetry
Closure 🖌
Common Fate

etc...

Affichage	Insertion	Format	Outils	Diaporama
✓ Normal Trieuse d Page de o Outils du Diaporan	le diapositiv commentair présentate na	ves es ur		
Masque				×.
En-tête e Afficher l Nuances	t pied de p es commen de gris	age taires		
Boîte à or ✓ III Pa III O III O III O Ra III O Pa	utils dette de mi bject Palette troonnaliser bum utils de réfé apport de ce dette de pro	se en forn e l'animatio rrence ompatibili ojet	ne on té	SC T#R
Bibliothè Barres d' Personna	que d'éléme outils liser les bai	ents rres d'outi	ls et les	menus
✓ Règle Repère Zoom				Þ

Design, sketching, prototyping

We may be asked to design/prototype a user interface or a specific interaction technique, e.g., one that is based on touch or gestures.

You won't have to write code but you can sketch it!

You may be explicitly asked to respect or follow some design guidelines or you may be asked to design it for certain users, e.g., novices or experts.

You may be asked to design it to address a specific problem, e.g., increase accuracy or reduce occlusion.

Example

Design an editor that helps UI designers to easily create state machines.

Specify the main functionality of the application and sketch its main screen.

You may be asked to create a storyboard to describe an interaction sequence.

You may be asked to create a storyboard to describe an interaction sequence.

Example: Draw a storyboard that describes the main steps of creating a state machine with your proposed interface.

You may be asked to redesign a user interface to reduce problems that you identified or extend it to satisfy some new user needs.

Exam 2013

Critique the interface by using three usability criteria (next lecture) and redesign it to fix the problems



exercise 2012

- An adaptive interaction technique adjusts CD gain of different screen areas depending on how often and for how long users visit them (at start all CD = 1)
- Assuming that very visited areas where the cursor moves slowly are dense, we reduce CD gain to make interaction more detailed
- We increase the CD of unvisited areas or areas the cursor moves fast as they likely do not contain interesting targets
- We show visual feedback of "dense" areas and the algorithm continues to adapt



What are drawbacks of the technique and solutions?

Other examples

exercise 2012-B : Feedback/Feedfwd



Both gray-out buttons for impossible actions ("Stop") and list of history

Where users can input text is clear (text box)

- Clicking options clearer in 2 (buttons look like buttons and not images)
- 2 has a better grouping of actions to guide users in what to use (e.g. back very close to fwd)
- In 2 attention is attracted by larger button

exercise 2012-B : Gestalt laws



Similarity: the first 2 icons similar Shape and Color and different from the rest because of colour

Proximity: not really followed

Bad Closure: targets not grouped and boundaries not visible **Symmetry:** The backward and forward buttons



Similarity: the first 2 icons similar in Shape and Color BUT their actual button shape is different, making grouping weaker

- **Similarity:** all buttons look like buttons (including the "g" which in top does not look like a widget)
- **Proximity:** the first 2 buttons are closer together than all the rest, thus a group
- **Closure:** the first 2 buttons are inside an enclosure (making them grouped together as related). All other buttons also enclosed to show individual functionality and clear boundaries.